

Heizmedium *PWW*

Technische Daten und Abmessungen (Gerätetyp A)

Typ	Drehzahl	Luftvolumenstrom	Heizleistung PWW 80/60 °C bei 15°C Eintrittstemperatur		Schalldruckpegel (5m) dB(A)	A	B	C	D	E	G	Gewicht kg
	U/min		m³/h	Q in kW								
Typ A-12	14	1.260	7,70	32,8	4	460	330	500	328	300	380	19,4
	900	788	5,91	36,9	40							
Typ A-13	1.400	1.208	10,34	40,0	44	460	330	500	328	300	380	19,8
	900	735	7,63	45,3	40							
Typ A-14	1.400	1.155	12,32	46,1	44	460	330	500	328	300	380	20,4
	900	683	8,69	52,2	40							
Typ A-22	1.400	2.835	15,05	30,5	47	560	430	500	428	400	480	25,1
	900	1.785	11,68	34,1	41							
Typ A-23	1.400	2.730	20,89	37,3	47	560	430	500	428	400	480	26,0
	900	1.733	15,96	41,9	41							
Typ A-24	1.400	2.678	23,65	40,8	47	560	430	500	428	400	480	27,0
	900	1.701	17,88	45,7	41							
Typ A-32	1.400	4.620	28,01	32,7	52	660	530	525	528	500	580	33,7
	900	2.940	21,73	36,6	43							
Typ A-33	1.400	4.463	32,60	36,3	52	660	530	525	528	500	580	34,5
	900	2.835	24,99	40,7	43							
Typ A-34	1.400	4.358	38,14	40,6	52	660	530	525	528	500	580	36,1
	900	2.783	28,95	45,4	43							
Typ A-42	1.400	6.510	40,72	33,3	55	760	630	515	628	600	680	39,1
	900	4.095	31,32	37,3	47							
Typ A-43	1.400	6.195	46,86	37,1	55	760	630	515	628	600	680	40,8
	900	3.938	35,87	41,6	47							
Typ A-44	1.400	6.090	53,18	40,5	55	760	630	515	628	600	680	43,1
	900	3.885	40,36	45,3	47							
Typ A-52	1.400	9.450	47,47	29,7	62	860	730	535	728	700	780	49,6
	900	5.985	37,06	33,1	51							
Typ A-53	1.400	9.240	61,46	34,4	62	860	730	535	728	700	780	52,0
	900	5.880	47,43	38,6	51							
Typ A-54	1.400	9.083	69,73	37,4	62	860	730	535	728	700	780	55,0
	900	5.775	53,32	42,0	51							
Typ A-62	900	8.820	68,23	37,6	55	960	830	535	828	800	880	57,8
	700	6.930	59,24	40,0	49							
Typ A-63	900	8.505	83,04	43,5	55	960	830	535	828	800	880	61,0
	700	6.563	70,57	46,4	49							
Typ A-64	900	8.295	87,12	45,7	55	960	830	535	828	800	880	63,2
	700	6.405	73,79	48,6	49							